

# CERTIFICATE OF COMPLIANCE

**Certificate Number** 20141213-E308146  
**Report Reference** E308146-20141212  
**Issue Date** 2014-December-13

**Issued to:** KNICK ELEKTRONISCHE MESSGERATE  
GMBH & CO KG  
BEUCKESTRASSE 22  
14163 BERLIN GERMANY

**This is to certify that  
representative samples of** PROCESS CONTROL EQUIPMENT FOR USE IN  
HAZARDOUS LOCATIONS  
See addendum page


Have been investigated by UL in accordance with the  
Standard(s) indicated on this Certificate.

**Standard(s) for Safety:** Standard No. ANSI/ISA 12.12.01, Nonincendive Electrical  
Equipment for Use in Class I and II, Division 2 and Class III,  
Divisions 1 and 2 Hazardous (Classified) Locations;  
Standard No. CAN/CSA C22.2 No. 213-M1987, Non-  
incendive Electrical Equipment for Use in Class I, Division 2  
Hazardous Locations

**Additional Information:** See the UL Online Certifications Directory at  
[www.ul.com/database](http://www.ul.com/database) for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's  
Certification and Follow-Up Service.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Assistant Chief Engineer, Global Inspection and Field Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please  
contact a local UL Customer Service Representative at [www.ul.com/contactus](http://www.ul.com/contactus)



# CERTIFICATE OF COMPLIANCE

**Certificate Number** 20141213-E308146  
**Report Reference** E308146-20141212  
**Issue Date** 2014-December-13

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Open Type Programmable Controllers for use in Hazardous Locations, Class I, Division 2, Groups A, B, C and D Hazardous Locations.

Loop-Powered Isolator and Loop-Powered Splitter

Loop-powered isolators for standard signals, 1 channel, types:

ProLine P22401P1

ProLine P22401P1-PX

ProLine P22401P1-SP-PX

ProLine P22401P1-PL-PX

ProLine P22401P1-PL-SP-PX

Loop-powered splitter for standard signals, 2 channels, type:

ProLine P22412P1

Loop-powered isolators for standard signals, 2 channels, types:


ProLine P22402P1

ProLine P22402P1-PX

ProLine P22402P1-SP-PX

ProLine P22402P1-PL-PX

ProLine P22402P1-PL-SP-PX



Bruce Mahrenholz, Assistant Chief Engineer, Global Inspection and Field Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at [www.ul.com/contactus](http://www.ul.com/contactus)

